

**chicco** Bongiorno mondo.  
Hello world.



Lifesavers Conference 2009  
Julie K. Robbins, CPSTI, Community & Advocate Relations Manager

---

---

---

---

---

---

---

---

**chicco** KeyFit Strada Booster



- ❖ With Backrest: 33-100lbs, 38-57"
- ❖ Without Backrest: 40-100lbs, 40-57"
- ❖ MSRP: 129.99
- ❖ 2<sup>nd</sup> Quarter 2009

---

---

---

---


---

---


---

---

**chicco** KeyFit Strada Booster



- ❖ Height adjustable Head/Torso
- ❖ Width adjustable Side wings
- ❖ Cupholder with adjustable angle
- ❖ EPS throughout



---

---

---

---

---

---


---

---

**chicco** Do we as CPS Technicians and Instructors know everything about all CRS and Vehicles?

**Absolutely NOT!**

**ALWAYS READ AND FOLLOW the instructions and labels**




---

---

---

---

---

---


---

---

---

---

**KF22 - Handle Hub Decal**      **KF30 - Handle Hub Decal**



**ALL KEYFIT BASES**

---

---

---

---

---

---

---

---

---

---


**chicco**

**HANDLE**

Handle has 3 LOCKED positions. To rotate to a new position, press both buttons near pivot.

**▲ BE SURE** handle is LOCKED in "CARRY" position before lifting carrier by handle. An unlocked handle could move unexpectedly, causing injury to child.

**▲ ALWAYS** place handle in one of the LOCKED positions when using Child Restraint in vehicle.



**▲ NEVER** hang toys or other objects from handle when using child restraint in vehicle. They could seriously injure a child in a sudden stop or crash.

---

---

---

---

---

---

---

---

---

---

**chicco**

**SHOULDER BELT LOCKOFF**

The Shoulder Belt Lockoff is used when installing the Base using your vehicle belts. It locks the vehicle shoulder belt in place, ensuring a stable, secure Base installation.

Shoulder belt lockoff

- Do not put the shoulder belt in the locked mode.
- With vehicle belt tight, position the shoulder belt under the Shoulder Belt Lockoff that is on the opposite side of the buckle.
- Firmly slide shoulder belt into the lockoff. (Optional: Once the base is installed tightly, the shoulder belt can be put in the locked mode. See vehicle owner's manual or label on seat belt for more information.)

Refer to "Installation Using Vehicle Belt" on page 22 for detailed installation instructions.

---

---

---

---

---

---

---

---

---

---

---

---

**chicco**

**INSTALLATION USING LATCH**

LATCH or Vehicle Belt? This Child Restraint can be safely installed using Vehicle Belt or LATCH. Use the method that results in the MOST SECURE installation in your vehicle.

Angle

- Remove LATCH Connectors from storage pockets while lifting up on LATCH Release Lever.
- Position Base in forward facing vehicle seat with Recline Foot against seat back.
- Adjust Base Angle by pushing Recline Buttons while lifting Base. Angle is correct when Bubble is between arrows.
- Attach LATCH Connectors by pushing them firmly onto vehicle LATCH Anchor Bars. Verify connection is secure by pulling firmly on LATCH straps.

LATCH anchors

This child restraint base is designed to be used with lower LATCH anchors at the standard spacing (11 inches) ONLY. Refer to vehicle owner's manual for information about LATCH and child restraint installation positions.

---

---

---

---

---

---

---

---

---

---

---

---

**chicco**

**How You Can Help Us Help You**

- Take Pictures!
- Provide Year, Make, Model of Vehicle
- Provide Model and Serial Numbers of CR
- Provide Detailed Descriptions
- Encourage Consumers to contact Customer Service: 877-4-CHICCO

---

---

---

---

---

---

---

---

---

---

---

---



Comments, Concerns, Questions are  
Welcome!

- ❖ Ideas for Improvement
- ❖ Issues with Instructions
- ❖ Misuse Found in the Field
- ❖ Request a KeyFit for demonstration/training
- ❖ Request a presentation

Contact:  
julier@chiccousa.com



---

---

---

---

---

---

---

---